



THE ULTIMATE POWER SOURCE®

NO MATTER THE PROBLEM, OPTIMA® BATTERIES HAVE THE POWER TO SOLVE IT



OPTIMA® REDTOP®

THE ULTIMATE STARTING BATTERY

The OPTIMA REDTOP high-performance AGM Battery is designed for starter applications. It's ideal for tuned and street cars, and other high-performance applications. It's even powerful enough to start generators while having small space requirements.

RECOMMENDED APPLICATIONS:



HIGH-PERFORMANCE



EXCESSIVE VIBRATION



EXTREME HEAT OR COLD



AGRICULTURE



OPTIMA® BLUETOP®

THE ULTIMATE MARINE & RV BATTERY

The OPTIMA BLUETOP high-performance AGM Battery is the perfect marine battery for boats with trolling motors and extensive electronic systems and works well with recreational vehicles with comfort features that tend to drain batteries quickly.

RECOMMENDED APPLICATIONS:



FISHING



POWER BOATS



SAILBOATS



RV/MOTORHOMES



OPTIMA® YELLOWTOP®

THE ULTIMATE DUAL-PURPOSE BATTERY

The OPTIMA YELLOWTOP high-performance AGM Battery is a dual-purpose battery for starter and cyclic applications. It is ideal for vehicles with high-demand electronics, commercial vehicles, heavy equipment and special applications like emergency vehicles. You can rely on this battery to provide ultimate starting and deep-cycle power.

RECOMMENDED APPLICATIONS:



HEAVY MACHINERY



OFF-ROAD/ 4X4



HEAVY-DUTY



EXTREME LOAD-LADEN

YELLOWTOP®

THE ULTIMATE DUAL-PURPOSE BATTERY



ETN	SHORT CODE	TYPE	BCI GROUP	LAYOUT	TERMINAL	ELECTRICAL RATINGS				LENGTH	WIDTH	HEIGHT	WEIGHT
						CCA A	CA (0°C) A	RC (25A) Minutes	C20 Capacity Ah				
851 187 000 888 2	YT S 5.5	Dual Power	D31A	8	1	975	1125	155	75	325	165	238	27.9
837 327 000 888 2	YT R 5.0	Dual Power	D27F	0	1	845	1025	140	66	309	172	219	21.5
812 254 000 888 2	YT S 4.2	Dual Power	D34	1	1	765	870	120	55	254	175	200	20.3
814 254 000 888 2	YT U 4.2	Dual Power	D34/78	1	1 & 21	765	870	120	55	254	175	200	20.6
840 222 000 888 2	YT R 3.7	Dual Power	D35	0	1	660	810	98	48	237	171	197	17
871 176 000 888 2	YT S 2.7	Dual Power	D51	1	1	460	575	66	38	237	129	227	12.5
870 176 001 888 2	YT S 2.7 J	Dual Power	DS46B24R	1	3	460	575	66	38	237	129	227	12.4
873 176 000 888 2	YT R 2.7	Dual Power	D51R	0	1	460	575	66	38	237	129	227	12.5
872 176 000 888 2	YT R 2.7 J	Dual Power	D51R	0	3	460	575	66	38	237	129	227	12.4
818 356 000 888 2	YT S 2.1	Dual Power	6 Volt	8	1	765	870	120	55	252	90	206	10.6

REDTOP®

THE ULTIMATE STARTING BATTERY



ETN	SHORT CODE	TYPE	BCI GROUP	LAYOUT	TERMINAL	ELECTRICAL RATINGS				LENGTH	WIDTH	HEIGHT	WEIGHT
						CCA A	CA (0°C) A	RC (25A) Minutes	C20 Capacity Ah				
801 287 000 888 2	RT C 4.2	Starter	34C	8	1	815	1000	100	50	254	175	200	18.5
802 250 000 888 2	RT S 4.2	Starter	34	1	1	815	1000	100	50	254	175	200	18
803 251 000 888 2	RT R 4.2	Starter	34R	0	1	815	1000	100	50	254	175	200	18
804 250 000 888 2	RT U 4.2	Starter	34/78	1	1 & 21	815	1000	100	50	254	175	200	18.4
878 209 000 888 2	RT F 4.2	Starter	78	1	21	815	1000	100	50	254	185	184	18
808 250 000 888 2	RT V 4.2	Starter	34	1	1 & 21	815	1000	100	50	254	175	200	18.5
820 255 000 888 2	RT S 3.7	Starter	25	1	1	730	910	90	44	237	171	197	15.6
835 255 000 888 2	RT R 3.7	Starter	35	0	1	730	910	90	44	237	171	197	15.6
822 255 000 888 2	RT U 3.7	Starter	75/25	1	1 & 21	730	910	90	44	237	171	197	15.7
810 355 000 888 2	RT S 2.1	Starter	6 Volt	8	1	815	1000	100	50	252	90	206	8.9

BLUETOP®

THE ULTIMATE MARINE & RV BATTERY



ETN	SHORT CODE	TYPE	BCI GROUP	LAYOUT	TERMINAL	ELECTRICAL RATINGS				LENGTH	WIDTH	HEIGHT	WEIGHT
						CCA A	CA (0°C) A	RC (25A) Minutes	C20 Capacity Ah				
852 188 000 888 2	BT DC 5.5	Dual Power	D31M**	8	1 & S	975	1125	155	75	325	165	238	27.9
827 227 000 888 2	BT DC 5.0	Dual Power	D27M	1	1 & S	845	1000	140	66	309	172	221	24.4
816 253 000 888 2	BT DC 4.2	Dual Power	D34M*	1	1 & S	765	870	120	55	254	175	200	20.6
806 252 000 888 2	BT SLI 4.2	Starter	34M*	1	1 & S	815	1000	100	50	254	175	200	18.4

*34M AND D34M MODELS FIT GROUP SIZE 24 MARINE BOXES AND TRAYS **D31M MODEL FITS GROUP 27 MARINE BOXES AND TRAYS