



FEATURES:

XC Fastest cycle up to full rated capacity.

XC Highest initial capacity.

XC Highest total energy delivered over the life of the battery.



1675 Sampson Ave. Corona, CA 92879 951. 371.8090 | 1895 Tobacco Rd. Augusta, Georgia 30906 706.790.0218 | 717 North Belair Road Evans, Georgia 30809 706.868.0533

DEEP CYCLE BATTERIES

U.S. BATTERY MODEL	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	M.C.A. @ 32° F	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
						LENGTH	WIDTH	HEIGHT		

6 VOLT GOLF CAR & MULTI PURPOSE

US 1800XC2	208	157	-	107	392	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 2000XC2	220	172	-	115	445	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 2200XC2	232	181	-	122	474	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 125XC2	242	198	-	140	517	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 145XC2	251	213	-	154	562	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48

8 VOLT GOLF CAR & MULTI PURPOSE

Min. @ 56 Amps										
US 8VGCXC2	155	129	110	75	312	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	BLK/BLK	48
US 8VGCXC2	170	133	118	82	325	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VGCXC2	183	147	136	95	365	10 1/4 (260)	7 1/8 (181)	11 1/4 (286)	RED/RED	48
US 8VHATBXC2	205	170	164	115	435	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	RED/RED	48

6 VOLT GOLF, SWEEPER/SCRUBBER & MULTI PURPOSE

US 250XC2	255	217	-	159	570	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 250HCXC2	280	239	-	178	635	11 5/8 (295)	7 1/8 (181)	11 5/8 (295)	RED/RED	36
US 305XC2	290	245	-	182	660	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	BLK/BLK	18
US 305XC2	310	261	-	195	715	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US 305HCXC2	340	283	-	215	790	11 7/8 (302)	7 1/8 (181)	14 5/8 (371)	RED/RED	18
US L16EXC2	360	270	-	198	795	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	BLK/BLK	18
US L16XC2	385	297	-	225	865	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US L16HCXC2	420	323	-	250	965	12 7/16 (315) w/ handles	7 1/8 (181)	16 3/4 (425)	RED/RED	18
US 1 HCXC2	95	-	-	44	165	8 3/4 (222)	6 7/8 (175)	9 (175)	BLK/BLK	72
US 100DINXC2	247	199	-	135	560	9 5/8 (244)	7 1/2 (191)	10 7/8 (276)	RED/RED	48

12 VOLT GOLF, SWEEPER/SCRUBBER & MULTI PURPOSE

US 12VRXC2	155	122	-	77	292	14 (355) w/ handles	7 1/16 (179)	11 3/8 (289)	RED/RED	36
US 12VEXC2	145	115	-	62	270	14 (355) w/ handles	7 1/16 (179)	11 3/8 (289)	BLK/BLK	36
US 185XC2	200	158	-	106	398	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185HCXC2	220	172	-	117	443	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	RED/RED	14
US 185EXC2	185	144	-	93	355	15 5/8 (397)	7 1/16 (179)	14 7/8 (378)	BLK/BLK	14

8 VOLT MARINE

13-4-1 XC2	170	-	-	116	380	21 7/16 (555)	7 1/2 (191)	10 1/2 (267)	RUBBER	24
15-4-1 XC2	195	-	-	133	440	24 3/8 (619)	7 7/16 (189)	10 1/2 (267)	RUBBER	16
17-4-1 XC2	220	-	-	147	490	27 7/16 (698)	7 7/16 (189)	10 1/2 (267)	RUBBER	16
19-4-1 XC2	245	-	-	162	545	26 3/4 (679)	8 7/16 (216)	11 1/8 (282)	RUBBER	16

12 VOLT SWEEPER/SCRUBBER, MARINE & MULTI PURPOSE

CCA @ 0°F										
US 24 DCXC2	85	68	400	38	145	10 7/8 (276)	6 3/4 (171)	9 3/8 (238)	RED/RED	72
US 27 DCXC2	105	89	575	54	205	12 3/4 (324)	6 3/4 (171)	9 3/4 (248)	RED/RED	54
US 31 DCXC2	130	99	620	59	225	13 (330)	6 3/4 (171)	9 5/8 (243)	RED/RED	54

12 VOLT MULTI PURPOSE

8D-HCXC2	240	177	-	115	470	20 3/4 (527)	11 1/8 (283)	9 7/8 (251)	BLK/BLK	16
----------	-----	-----	---	-----	-----	--------------	--------------	-------------	---------	----

6 VOLT RENEWABLE ENERGY

US RE L16XC2	401	317	-	245	915	11 7/8 (302)	7 7/8 (181)	16 3/4 (425)	GRN/GRN	18
US REGC2HCXC2	242	194	-	136	507	10 1/4 (260)	7 1/8 (181)	11 7/8 (302)	GRN/GRN	48

2 VOLT RENEWABLE ENERGY

US RE L162VXC2	1100	962	-	845	2826	11 7/8 (302)	7 7/8 (181)	16 3/4 (425)	GRN/GRN	18
----------------	------	-----	---	-----	------	--------------	-------------	--------------	---------	----

LOW MAINTENANCE STARTING BATTERIES

BCI GROUP SIZE	U.S. BATTERY MODEL	C.C.A. @ 0° F	C.A. @ 32° F	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
					LENGTH	WIDTH	HEIGHT		

6 VOLT AUTOMOTIVE & COMMERCIAL

2E	2E	600	730	180	19 3/8 (492)	4 1/8 (105)	9 1/8 (232)	RUBBER	60
19L	19L	525	640	110	8 3/16 (208)	6 11/16 (170)	7 7/16 (189)	RUBBER	90

12 VOLT TRUCK - BUS - COMMERCIAL

17TF	17TF	625	765	150	17 1/16 (433)	6 15/16 (176)	8 (203)	RUBBER	42
------	------	-----	-----	-----	---------------	---------------	---------	--------	----

12 VOLT MILITARY ORDINANCE

6TL(mil)	6TMF	750	----	230	11 1/4 (286)	10 1/2 (267)	9 (229)	BLK/BRN	36
----------	------	-----	------	-----	--------------	--------------	---------	---------	----

DEEP
CYCLE
AGM

6, 8, & 12 Volt AGM - Sealed Non-spillable Batteries

U.S. BATTERY MODEL	AMP HOURS (20 hr. rate)	AMP HOURS (5 hr. rate)	TERMINALS	MINUTES @ 75 AMPS	MINUTES @ 25 AMPS	DIMENSIONS, Inches (mm)			COVER AND CASE	PALLET QTY
						LENGTH	WIDTH	HEIGHT		

6 VOLT AGM DEEP CYCLE

US AGM 2000	210	177	DUAL	120	460	10.24 (260)	7.09 (180)	10.79 (274)	RED/RED	32
US AGM 6V27	215	182	T11	112	500	12.05 (306)	6.61 (168)	8.98 (228)	RED/RED	24
US AGM 2224	225	195	F14	142	510	10.2 (260)	7.09 (180)	9.9 (252)	RED/RED	32
US AGM 6V260	260	220	F14	156	560	10.2 (260)	7.09 (180)	10.7 (272)	RED/RED	32
US AGM 305	340	306	DUAL	240	790	11.61 (295)	7 (178)	14.3 (364)	RED/RED	12
US AGM L16	414	360	DUAL	275	984	11.61 (295)	7 (178)	16.65 (423)	RED/RED	12

8 VOLT AGM DEEP CYCLE

MINUTES @ 56 AMPS										
US AGM 8V170	180	149	DUAL	120	381	10.2 (260)	7.17 (182)	11.3 (286)	RED/RED	40

12 VOLT AGM DEEP CYCLE

US AGM 24	90	82	T6-A	43	175	10.24 (260)	6.61 (168)	8.43 (214)	RED/RED	36
US AGM 27	112	98	DUAL	55	220	12.05 (306)	6.61 (168)	9.17 (233)	RED/RED	36
US AGM 31	117	96	F12	45	207	12.9 (328)	6.77 (172)	8.66 (220)	RED/RED	30
US AGM 12V150	150	133	T11	90	323	12.87 (327)	7.09 (180)	10.79 (274)	RED/RED	24
US AGM 12V240	230	203	DUAL	145	522	15.03 (382)	7.04 (179)	14.5 (370)	RED/RED	10
US AGM 8D	308	252	F14	180	738	20.5 (521)	10.6 (268)	8.86 (225)	RED/RED	12